

Container Handler

Used Container Handler West Virginia - Container handlers are also called container ships and cargo ships since they transport loads in sizeable intermodal containers. This shipping method is known as containerization. They are commonly utilized as a means of commercial freight transport often used to transport non-bulk forms of seagoing cargo. The capacity of container ships is measured in units equivalent to twenty-foot equivalent loads. Most loads are a mix of 20' and 40' containers. Container ships are responsible for transporting roughly ninety percent of non-bulk items across the globe. As one of the largest commercial sea-worthy vessels, container ships are the main rival of oil tankers among the largest ships on the ocean. There are two main categories for dry cargo which are break-bulk and bulk cargo. Grain and coal fall into the bulk cargo category. They are often moved in their raw form, package-free in large volumes in the hull of the ship. Break-bulk cargo typically is made up of manufactured items that are shipped in packaging. Prior to containerization being invented in the 1950s, break-bulk materials were loaded, secured, unlashed and unloaded one piece at a time from the ship. When the cargo was grouped into containers, there were approximately 1000-3000 cubic feet of cargo that can be simultaneously moved after each unit has been standardized and secured. Overall efficiency has largely increased with break-bulk cargo shipping. Costs have been reduced to around 35% and shipping time has been reduced by 84%! Approximately 90% of non-bulk items were shipped in containers in 2001. The first cargo ships were born in the 1940s as redesigns from World War II tankers. Cargo ships do not use individual dividers, holds or hatches that are a part of traditional container ships. The typical container ship's hull is a basically a large warehouse that is divided by vertical guide rails into cells. The cargo in the containers is held by these specially designed cells. Most shipping containers are constructed from steel; however, additional materials including plywood, fiberglass and wood are used. Designed to be completely transferred to and from trains, semi-trailers, trucks, coastal carriers and more, there is a variety of container types that are categorized by their function and size. Containerization has revolutionized the shipping industry; however, it did not start out in the easiest fashion. Railway companies, ports and shippers were initially concerned about the extensive costs associated with building the railway infrastructure and ports required to accommodate container ships, along with moving the containers via road and rail. Numerous trade unions were concerned that containers would affect port jobs and manual labor associated with cargo handling for dock and port workers. There was a decade of legal battles prior to the container ships starting international service. By 1966, after the first container liner service began from Rotterdam, Netherlands to the USA, cargo shipping was transformed. Initially, it took days to unload and load traditional cargo vessels. Container ships have transformed timelines by only requiring a few hours for loading and unloading. Shipping times have been shortened in between ports extensively along with labor finances. It only takes 3 weeks to have materials delivered from Europe to India as opposed to the months it used to require. There is generally less damage to goods due to less handling. Less cargo shifting during a voyage is also beneficial. Containers are sealed prior to shipping and opened only once they arrive at their destination, resulting in less theft and disruption. There has been greater international trade growth due to the reduced shipping expenses and travel time delivered by container ships. Cargo that was previously shipped in bags, bales, cartons, barrels or crates now arrives in sealed containers from the factory. Scanning machines work with computers to trace the product code on the contents. Amazingly, technology has advanced with this accurate tracking system to be so exact that a 2-week voyage can be timed for arrival with accuracy less than 15 minutes! This time management has helped with manufacturing times and guaranteeing delivery. Raw materials show up in sealed containers from factories in under an hour prior to being used in the manufacturing industry; resulting in fewer inventory expenses and greater accuracy. Boxes are provided by shipping companies to the exporters to facilitate loading merchandise. Items are delivered into the docks by road or rail or a combination to be loaded onto cargo

ships. It used to take huge groups of men and numerous hours to fit cargo into different holds prior to containerization. The ship relies on cranes either on the pier or installed on board to organize the containers accurately. Once the hull has been completely loaded, more containers can be secured onto the deck. Efficiency has been one of the main design elements for cargo ships. Containers may travel on break-bulk vessels. However, cargo holds that have been dedicated to container ships have been carefully built to speed up the loading and unloading process and designed to keep containers secure while traveling the ocean. A specially designed hatch creates openings to access the main cargo holds from the deck. A raised steel apparatus called the hatch coaming surrounds these openings that are found along the cargo hold breadth. The hatch coamings have hatch covers located on them. Tarps and wooden boards held down the battens and secured the hatches until the 1950s. These days, hatch covers often consist of solid metal plates that are lifted on and off the ship with cranes. Additional hatch models use hydraulic rams and articulated mechanisms for closing and opening. Cell guides are another main component within container ship design. Attached to the cargo hold in the ship, cell guides are vertical pieces of metal that help organize the cargo. These guide the containers into certain locations and offer travel support on the high seas. The container ship design relies on cell guides so much that organizations as the United Nations Conference on Trade and Development use them to differentiate between regular break-bulk cargo ships and container ships. There are three dimensions used in cargo plans to determine the position of the container on board the ship. The bay is the first coordinate, starting at the front of the container ship and increases aft. The second coordinate is the tier. The first tear begins in the lower portion of the cargo holds with the second tier found on top of the first tier and continuing in that fashion. The row is the third coordinate. Rows found on the port side of the ship exhibit even numbers and those located on the starboard side are given odd numbers. The cargo situated near the centerline showcases lower numbers and as the cargo increases further from the center, the numbers get higher. Container handlers carry 20, 40 and 45 foot containers. The biggest sizes only fit above the deck. The forty-foot containers comprise most of the load or roughly 90% of container shipping. Approximately 90% of the freight moves across the globe with container shipping. It is estimated that 80% of global freight travels with 40-foot containers.