

Telehandler / Zoom Boom

Used Telehandler West Virginia - Telehandlers are commonly known by a variety of names such as Cherry pickers, telescopic handlers, boom lifts and teleporters. This industrial machine is commonly used in a variety of industries and in agriculture. This machine functions similarly to a crane and a forklift with the ability to extend upward and forward. Numerous attachments can be placed at the end of the articulating boom to conduct a variety of different jobs. Different attachments such as a bucket, pallet forks, a muck grab or a winch can help the machine complete many jobs. The most common telehandler attachment is the pallet forks. These attachments help the operator transport different sized loads to many locations that would be considered unreachable with a traditional forklift. Telehandlers allow cargo pallets to be transported from trailers and placed on racking, rooftops or other difficult to reach locations. Normally, high rooftop applications would require the use of a crane; however, telehandlers can complete this task more efficiently. Of course, it isn't always affordable or practical to use secondary equipment or a crane to complete certain tasks. A bucket or bucket grab is the most popular telehandler attachment in the agricultural industry. Relocating items from hard to reach areas that cannot rely on a wheeled loader or a backhoe loader give telehandlers a significant advantage. Telehandlers can directly access trailer units with high sides, hoppers or applications that would typically need a conveyor or loading ramp. Having one item to complete a variety of jobs saves time, money and storage space. Telehandlers commonly work alongside a crane jib. Various attachments may be used including rotators, dirt buckets, grain buckets and power booms. Three-point linkage and power take-off can be used with agricultural models to make this machine particularly capable. Interestingly enough, the machines' main advantage is also its' biggest limitation. The boom raises or extends with heavy loads, acting as a lever. Even with rear counterweights, this machine may become unstable from time to time; decreasing the lift capacity when the distance between the center of the load and the front of the wheels or the working radius increases. If the machine works as a single boom loader instead of using twin arms while carrying a large load, there is a chance that weakness can occur even in the most carefully designed units. For instance, a telehandler with a five thousand pound capacity may be capable of safely lifting as little as four hundred pounds fully extended with a low boom angle with a retracted boom. Raising the same piece of equipment 70 degrees could allow this machine with a five thousand pound lift capability and retracted boom to support up to ten thousand pounds. These machines are equipped with a load chart to help outline which tasks are safely possible. These charts take the boom height, angle and weight into account. Newer telehandler models rely on computers and sensors to monitor the machine. The operator cannot continue once the machine's limits have been reached. They are warned and cut off from accessing the control input. There are front stabilizers that can drastically enhance the machine's lifting capacity while it is stationary. A mobile crane can also use a bucket is another option consisting of a stabilized rotary joint found between upper and lower frames. There are compact telehandler models that differ in boom design, size, reach and weight. If the machine weighs in at eleven thousand pounds or less, it can be part of the compact category. Compact units have a two-stage boom compared to larger machines that feature three or four boom designs. A low pivot boom ensures better operator visibility for transporting loads on compact units. Compact models are skinnier and have thinner dimensions. The reach capacity for compact units is between thirteen to twenty feet and these units offer a lift capacity from five to seven thousand pounds. These versatile machines make the compact telehandler extremely popular. It may be used as a tool carrier or a pick and place machine. This machine is often used in locations that are cramped and tight. Residential applications are common as contractors relish their useful nature with framing applications and where height restrictions come into play. These units can be useful for accessing internal building locations. Compact telehandlers are commonly used in nurseries, landscaping, multi-story construction, building strip malls and garages, masonry, erecting steel and more. Telehandlers are employed by agribusiness and farming applications to complete many jobs. Telehandlers can be found with two and fourwheel drive and crab steering capabilities. The unit can travel over longer ranges at higher speeds with twowheel drive, making it ideal for moving throughout job sites. The four-wheel drive models offer the ability to traverse more difficult terrain and provide a tighter turning radius. Crab steering increases overall maneuvering and enables the front and back wheels to move 45 degrees to the left or the right. Compact telehandlers have varying cab environments. On the lower-end models, a rollover protective cage structure is in place for safety. Higher models come with a heater, a completely enclosed cab, defroster and windshield wiper. All compact telehandler cabs are spacious to accommodate the operator as comfortable as possible. Extra amenities including air conditioning, satellite radio, suspension seats, tilt steering and cup holders are available. The numerous attachment options are facilitated with high-pressure and high-flow auxiliary hydraulics. The different attachments allow the machine to be capable of many options. All of these attachments enable the machine to conduct a variety of jobs. Ground engaging work is often completed by compact units. It is easy to enjoy the benefits of a mini excavator by adding a simple bucket attachment to the telehandler. Light-duty to heavy-duty buckets can be attached for transferring material, side-shifting and rotating fork carriages are relied on for pick and place situations, augers for drilling post holes or planting trees or pier supports, truss booms for extending reach, crane hooks, brooms for sweeping and more. Skid steer attachments are being made for versatility and other compact telehandler designs.